FIX–

Applique en aluminium moulé disponibile en différentes finitions:
blanc, noir, or bruni,
aluminium poli, doré poli ou doré satiné. Disponible avec double émission up & down ou simple émission up indirecte. Dimmable TRIAC.



DOUBLE EMISSION

LAMPING

Source	LED board
Total power	2x6W
Emission	up+down
Switching	dimmable TRIAC
Tension	230V
Color temperature	2700K
Luminous flux	2x380lm
Typ CRI	85
Energy class	A+
Materials	aluminium
Notes	available also in 120V. Suggested dimmer: TECNEL TE7636 (dimming range: from ~45% to 100%) lamps are sold three by two
Net lamp weight	0,6 kg


Codes	*Structure*
FIM LWW 31	white
FIM LNW 31	black
FIM LLW 31	polished
FIM LOW 31	gold polished
FIM LGW 31	gold burnished
FIM LOS 31	gold frosted

PACKAGE

Package 01	Dimension: 18x15x14 cm / Gross weight: 1 kg

Certificazioni





SINGLE EMISSION

LAMPING

Source	LED board
Total power	6W
Emission	side emission
Switching	dimmable TRIAC
Tension	230V
Color temperature	2700K
Luminous flux	380lm
Typ CRI	85
Energy class	A+
Materials	aluminum
Notes	available also in 120V. Suggested dimmer: TECNEL TE7636 (dimming range: from ~45% to 100%) lamps are sold three by two
Net lamp weight	0,6 kg

Codes	*Structure*
FIM LWW 32	white
FIM LNW 32	black
FIM LLW 32	polished
FIM LOW 32	gold polished
FIM LGW 32	gold burnished
FIM LOS 32	gold frosted

PACKAGE

Package 01	Dimension: 18x15x14 cm / Gross weight: 1 kg

Certificazioni



