

ZIRKOL – L

ZIRKOL – L is a family of linear suspension lamps suitable for general and decorative lighting.

Anodized aluminium body and opal screen to a homogeneous lighting.

Light emission can be direct light and double light emission with high flux and different colour temperatures. Driver and dimmer interface included.



LINEAR 39.4" | DOWNLIGHT - 2700K

LAMPING

Source	linear LED
Total power	14.5W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	2700K
Luminous flux	833lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)


Codes

UZRL1610G15DBO
UZRL1610G15DNE
UZRL1610G15DOR

Structure

white
black
gold

Certificazioni



LINEAR 39.4" | DOWNLIGHT - 3000K

LAMPING

Source	linear LED
Total power	14.5W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	3000K
Luminous flux	882lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)



Codes

UZRL1610G15WBO
UZRL1610G15WNE
UZRL1610G15WOR

Structure

white
black
gold

Certificazioni



LINEAR 39.4" | DOWNLIGHT - 4000K

LAMPING

Source	linear LED
Total power	14.5W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	4000K
Luminous flux	980lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)



Codes

UZRL1610G15NBO
UZRL1610G15NNE
UZRL1610G15NOR

Structure

white
black
gold

Certificazioni



LINEAR 39.4" | UP-DOWNLIGHT - 2700K

LAMPING

Source	linear LED
Total power	29W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	2700K
Luminous flux	1666lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)


Codes

UZRL1710G15DBO
UZRL1710G15DNE
UZRL1710G15DOR

Structure

white
black
gold

Certificazioni



LINEAR 39.4" | UP-DOWNLIGHT - 3000K

LAMPING

Source	linear LED
Total power	29W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	3000K
Luminous flux	1764lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)


Codes

UZRL1710G15WBO
UZRL1710G15WNE
UZRL1710G15WOR

Structure

white
black
gold

Certificazioni



LINEAR 39.4" | UP-DOWNLIGHT - 4000K

LAMPING

Source	linear LED
Total power	29W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	4000K
Luminous flux	1960lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)



Codes

UZRL1710G15NBO
UZRL1710G15NNE
UZRL1710G15NOR

Structure

white
black
gold

Certificazioni



LINEAR 78.7" | DOWNLIGHT - 2700K

LAMPING

Source	linear LED
Total power	29W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	2700K
Luminous flux	1666lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)


Codes

UZRL1620G15DBO
UZRL1620G15DNE
UZRL1620G15DOR

Structure

white
black
gold

Certificazioni



LINEAR 78.7" | DOWNLIGHT - 3000K

LAMPING

Source	linear LED
Total power	29W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	3000K
Luminous flux	1764lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)



Codes

UZRL1620G15WBO
UZRL1620G15WNE
UZRL1620G15WOR

Structure

white
black
gold

Certificazioni



LINEAR 78.7" | DOWNLIGHT - 4000K

LAMPING

Source	linear LED
Total power	29W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	4000K
Luminous flux	1960lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)


Codes

UZRL1620G15NBO
UZRL1620G15NNE
UZRL1620G15NOR

Structure

white
black
gold

Certificazioni



LINEAR 78.7" | UP-DOWNLIGHT - 2700K

LAMPING

Source	linear LED
Total power	58W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	2700K
Luminous flux	3332lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)


Codes

UZRL1720G15DBO
UZRL1720G15DNE
UZRL1720G15DOR

Structure

white
black
gold

Certificazioni



LINEAR 78.7" | UP-DOWNLIGHT - 3000K

LAMPING

Source	linear LED
Total power	58W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	3000K
Luminous flux	3528lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)


Codes

UZRL1720G15WBO
UZRL1720G15WNE
UZRL1720G15WOR

Structure

white
black
gold

Certificazioni



LINEAR 78.7" | UP-DOWNLIGHT - 4000K

LAMPING

Source	linear LED
Total power	58W
Emission	diffused
Switching	dimmable 0-10V
Tension	110/277V
Color temperature	4000K
Luminous flux	3920lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	aluminum
Notes	RAL 9005 black RAL 9016 white shipped assembled round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 electrical cable length 16.4' 2 x adjustable metal cable length 9.8' (including ceiling attachments)

Codes

UZRL1720G15NBO
UZRL1720G15NNE
UZRL1720G15NOR

Structure

white
black
gold

Certificazioni

