

TRU PENDANT HORIZONTAL

Roberto Paoli



Sculptural, sleek, compact: two light panels compose a parallelepiped, leaving space for an empty slot, but concealing the light source through an optical effect. Made of aluminium, Tru provides indirect and diffuse light through two internal LED strips and an LED element on top. Equipped with a double dimmer for independent control of the two light sources.

DOWNLIGHT + DOWNLIGHT 2700K



LAMPING

Source	linear LED
Total power	54W
Emission	diffused
Switching	dimmable on cable, mono switch
Tension	120V
Color temperature	2700K
Luminous flux	3520lm
Typ CRI	85
IP class	20
Dimensions	3.5" x 4.3" x 68.9"
Materials	aluminium + PC
Notes	metal cable length 9.8', electric cable length 16.4', 3500K and 4000K available on request, extra cable on request, square cover plate included, integral driver dual capability TRIAC-ELV and 0-10V on request
Net lamp weight	9,9 lbs

Codes	*Structure*
TRU LWW 57	white
TRU LNN 57	black
TRU LDD 57	titan grey


PACKAGE

Package 01	Dimension: 8.7" x 6.3" x 74" inches / Net weight: 14,3 lbs

Certificazioni

Intertek

UPLIGHT + DOWNDOWNLIGHT 2700K



LAMPING

Source	linear LED
Total power	54W
Emission	diffused
Switching	dimmable on board, mono switch
Tension	120V
Color temperature	2700K
Luminous flux	3520lm
Typ CRI	85
IP class	20
Dimensions	3.5" x 4.3" x 68.9"
Materials	aluminium + PC
Notes	metal cable length 9.8', electric cable length 16.4', 3500K and 4000K available on request, extra cable on request, square cover plate included, integral driver dual capability TRIAC-ELV and 0-10V on request
Net lamp weight	9,9 lbs

Codes	*Structure*
TRU LWW 55	white
TRU LNN 55	black
TRU LDD 55	titan grey


PACKAGE

Package 01	Dimension: 8.7" x 6.3" x 74" inches / Net weight: 14,3 lbs

Certificazioni

Intertek

DOWNLIGHT + DOWNLIGHT 3000K



LAMPING

Source	linear LED
Total power	54W
Emission	diffused
Switching	dimmable on board, mono switch
Tension	120V
Color temperature	3000K
Luminous flux	3520lm
Typ CRI	85
IP class	20
Dimensions	3.5" x 4.3" x 68.9"
Materials	aluminium + PC
Notes	metal cable length 9.8', electric cable length 16.4', 3500K and 4000K available on request, extra cable on request, square cover plate included, integral driver dual capability TRIAC-ELV and 0-10V on request
Net lamp weight	9,9 lbs

Codes	*Structure*
TRU LWW 5C	white
TRU LNN 5C	black
TRU LDD 5C	titan grey


PACKAGE

Package 01	Dimension: 8.7" x 6.3" x 74" inches / Net weight: 14,3 lbs

Certificazioni

Intertek

UPLIGHT + DOWNLIGHT 3000K



LAMPING

Source	linear LED
Total power	54W
Emission	diffused
Switching	dimmable on board, mono switch
Tension	120V
Color temperature	3000K
Luminous flux	3520lm
Typ CRI	85
IP class	20
Dimensions	3.5" x 4.3" x 68.9"
Materials	aluminium + PC
Notes	metal cable length 9.8', electric cable length 16.4', 3500K and 4000K available on request, extra cable on request, square cover plate included, integral driver dual capability TRIAC-ELV and 0-10V on request
Net lamp weight	9,9 lbs

Codes	*Structure*
TRU LWW 5A	white
TRU LNN 5A	black
TRU LDD 5A	titan grey

PACKAGE

Package 01	Dimension: 8.7" x 6.3" x 74" inches / Net weight: 14,3 lbs

Certificazioni

Intertek