

ALYA

Gabriele Rosa

Leichte LED-Pendelleuchte für 70 % Up-Light und 30 % Down-Light, Arme aus fließgepresstem Aluminium, mittlerer Leuchtenkörper aus Aluminiumdruckguß, Diffusor aus opalweißem Methacrylat. Erhältlich in matt weiß oder matt schwarz. Lieferbar auch mit Fernbedienung.



REMOTE CONTROL LED

LAMPING

Source	linear LED
Total power	37,5W
Emission	uplight, diffused
Switching	dimmable, 1-10V, remote
Tension	110/240V
Color temperature	3000K
Luminous flux	2130lm (source luminous flux)
Typ CRI	83
Energy class	A+
Dimensions	40x100x100
Materials	aluminium + PC
Notes	cable length max 2,5m
Net lamp weight	3 kg

Codes

ALY LWW 52

ALY LNN 52

Structure

white


black

PACKAGE

Package 01

Dimension: 16x64x47 cm / Gross weight: 4,5 kg

Certificazioni



DALI PUSH 220V

LAMPING

Source	linear LED
Total power	37,5W
Emission	uplight, diffused
Switching	dimmable, DALI push
Tension	230V
Color temperature	3000K
Luminous flux	2130lm (source luminous flux)
Typ CRI	85
Energy class	A+
Materials	aluminium + PC
Notes	cable length max 2,5m

Codes

ALY LWW 53
ALY LNN 53

Structure

white
black

Certificazioni

