

MINIFLUX OPAL

MINIFLUX ist ein modulares LED-System für dekorative und Akzentbeleuchtung des Innen- und Außenbereichs.

Hochemissions-LED-Streifen (24V DC) in einem Aluminiumprofil.

Diffusor polycarbonat opal für eine homogene Beleuchtung.

Transparente Polycarbonat-Halterungen erlauben eine flexible Befestigung.

Miniflux ist in verschiedenen Längen und Farbtemperaturen verfügbar.

LED-Driver sind nicht enthalten.



1M | 3000K

LAMPING

Source	Linear LED
Total power	15W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	905lm
Initial luminaire efficacy	> 60lm/W
Initial chromaticity	SDCM < 3
Typ cri	97
Energy class	A+
Ip class	65
Dimensions	ø2x103cm
Materials	Polycarbonate
Ambient temperature range	- 20°C / 50°
Performance ambient temperature	25°
Mechanical impact protection code	IK08
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Drivers 24VDC, Miniflux accessories, joint, PG, feeding, end-cap
Net lamp weight	0,31 kg

Codes

BBOK0910G26WPO

Structure

opal white

PACKAGE


Package 01

Dimension: 120x8,5x4 cm / Gross weight: 0,5 kg

Certificazioni



NEMO STUDIO



1M | 4000K

LAMPING

Source	Linear LED
Total power	15W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Initial luminaire efficacy	> 60lm/W
Initial chromaticity	SDCM < 3
Typ cri	94
Energy class	A+
Ip class	65
Dimensions	ø2x103cm
Materials	Polycarbonate
Ambient temperature range	- 20°C / 35°
Performance ambient temperature	25°
Mechanical impact protection code	IK10
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Drivers 24VDC, Miniflux accessories, joint, PG, feeding, end-cap
Net lamp weight	0,31 kg

Codes

BBOK0910G26NPO

Structure


opal white

PACKAGE

Package 01

Dimension: 120x8,5x4 cm / Gross weight: 0,5 kg

Certificazioni



2M | 3000K

LAMPING

Source	Linear LED
Total power	30W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Initial luminaire efficacy	> 60lm/W
Initial chromaticity	SDCM < 3
Typ cri	97
Energy class	A+
Ip class	65
Dimensions	ø2x201cm
Materials	Polycarbonate
Ambient temperature range	- 20°C / 50°
Performance ambient temperature	25°
Mechanical impact protection code	IK08
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Drivers 24VDC, Miniflux accessories, joint, PG, feeding, end-cap
Net lamp weight	0,49 kg

Codes

BBOK0920G26WPO

Structure


opal white

PACKAGE

Package 01

Dimension: 220x8,5x4 cm / Gross weight: 0,31 kg

Certificazioni



2M | 4000K

LAMPING

Source	Linear LED
Total power	30W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Initial luminaire efficacy	> 40lm/W
Initial chromaticity	SDCM < 3
Typ cri	94
Energy class	A+
Ip class	65
Dimensions	ø2x201cm
Materials	Polycarbonate
Ambient temperature range	- 20°C / 35°
Performance ambient temperature	25°
Mechanical impact protection code	IK10
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 0,5m; driver not included
Customization options	Lengths
Accessories	Drivers 24VDC, Miniflux accessories, joint, PG, feeding, end-cap
Net lamp weight	0,49 kg

Codes

BBOK0920G26NPO

Structure

opal white

PACKAGE

Package 01

Dimension: 220x8,5x4 cm / Gross weight: 1,75 kg

Certificazioni

