
ELLISSE PENDANT DOUBLE MEGA

Federico Palazzari


Realised in various versions through an innovative technology developed by Nemo for coupling extrusions, Ellisse guarantees diffused direct and indirect lighting with the LED housed within the structure while remaining unobtrusive. The design is linear and contemporary, while an elegant black marble base becomes a pedestal for the floor version.



2700K

LAMPING

Source	Linear LED
Total power	90W
Emission	diffused uplight (major), diffused downlight (mega)
Switching	dimmable 1-10V
Tension	110-240V
Color temperature	2700K
Luminous flux	2825+1850lm (real luminous output)
Typ CRI	85
IP class	20
Materials	Aluminium
Notes	adjustable cable length from 2,5m to 0,4m, DALI version on request, TRIAC VERSION on request
Net lamp weight	5,5 kg



Codes	*Structure*
ELP LW2 5A	white
ELP LN2 5A	black
ELP LO2 5A	gold painted

PACKAGE

Package 01	Dimension: 14x101x201 cm / Gross weight: 7,5 kg

Certificazioni

3000K

LAMPING

Source	Linear LED
Total power	90W
Emission	diffused uplight (major), diffused downlight (mega)
Switching	dimmable 1-10V
Tension	110-240V
Color temperature	3000K
Luminous flux	2825+1850lm (real luminous output)
Typ CRI	85
IP class	20
Materials	Aluminium
Notes	adjustable cable length from 2,5m to 0,4m, DALI version on request
Net lamp weight	5,5 kg

Codes	*Structure*
ELP LWW 5A	white
ELP LNW 5A	black
ELP LOW 5A	gold painted

PACKAGE

Package 01	Dimension: 14x101x201 cm / Gross weight: 7,5 kg

Certificazioni



